



TECHNICAL SPECIFICATIONS

SPECIFICATION

Sensor	1/2.8-inch-high quality HD CMOS sensor
Effective Pixels	16: 9, 2.07 megapixel
Video Format	HDMI/SDI 1080P60/50/30/25/59.94/29.97; 1080I60/50/59.94; 720P60/50/30/25/59.94/29.97
Optical Zoom	20X f=5.5-110mm
View Angle	3.3°(tele) 54.7°(wide)
AV	F1.6 - F3.5
Digital Zoom	10X
Minimum Illumination	0.1Lux
DNR	2D & 3D DNR
White Balance	Auto / Manual/ One Push/ 3000K/ 4000K/5000K/6500K
Focus	Auto/Manual/One key focus
Aperture/Electronic Shutter	Auto / Manual
BLC	ON/OFF
WDR	OFF/ Dynamic Level Adjustment
Video Adjustment	Brightness, Color, Saturation, Contrast, Sharpness, B/W mode, Gamma curve
SNR	>55dB



INPUT/OUTPUT INTERFACE

Video Interfaces	SDI, HDMI, LAN (NDI & POE), RS232 (In & Out), RS485, A-IN
Video output interface	HDMI, SDI, LAN,
Video Compression Format	H.264, H.265, Dual stream output
Control Protocol	VISCA/Pelco-D/Pelco-P;Baud Rate:115200/9600/4800/2400bps
Audio Input Interface	A-IN: Double track 3.5mm linear input;
Audio Compression Format	AAC/MP3/G.711A Audio compression
HD IP Interface	100M IP Port(10/100BASE-TX); Support VISCA protocol control through IP port
Network Protocol	RTSP, RTMP, ONVIF, GB/T28181, NDI
Power Interface	HEC3800 Outlet (DC12V)
Supply Adapter	AC110V-AC220V to DC12V/1.5A
Input Voltage	DC12V±10%
Input current	1A (Max)
Consumption	12W (Max)

PTZ PARAMETER

Pan/Tilt Rotation	±170°, -30°~+90°
Pan Control Speed	0.1 -60°/sec
Tilt Control Speed	0.1-30°/sec
Preset Speed	Pan: 60°/sec, Tilt: 30°/sec
Preset Number	255 presets (10 presets by remote controller)

OTHER PARAMETER

Storage Temperature	-10°C~+60°C
Storage Humidity	20%~95%
Working Temperature	-10°C~+50°C
Working Humidity	20%~80%
Dimension	150mmX150mmX167.5mm
Weight	1.4KG
Remote Operation (IP)	Remote Upgrade, Reboot, and Reset
Accessories	12V/1.5A power supply, RS232 cable, remote control, manual, warranty card, Bracket

